

FITT aliflex superflex



Tubo per uso gravoso installato su macchinari agricoli e dell'industria alimentare.

FITT Aliflex Superflex ha una elevata flessibilità per garantire un uso facile in tutti i settori dell'agricoltura. Resistente allo schiacciamento è certificato per l'aspirazione e mandata di liquidi alimentari.

Struttura: Tubo spiralato in PVC con spirale di rinforzo in PVC rigido anti-urto.

Temperatura di utilizzo: -10°C / +60°C

- Elevata flessibilità.
- Elevata resistenza allo schiacciamento.
- Elevata durabilità.

Heavy-duty hose for installation on agricultural machinery and of food sector.

FITT Aliflex Superflex has a high flexibility to guarantee and easy usage in all the agricultural sectors. Resistant to crushing, is certified for the suction and delivery of liquid foods.

Structure: PVC spiral hose with reinforcement spiral in rigid shock-resistant PVC.

Temperature of use: -10°C / +60°C

- High flexibility.
- High crushing resistance.
- High durability.



REACH¹
conforme
REACH¹
compliant



RoHS²
conforme
RoHS²
compliant



Senza
IPA³
PAH³
free



Senza ftalati⁴
formula <0,1%
Phthalate free⁴
formulation <0,1%



MOCA - Conforme al Regolamento Europeo 10/2011 per i Simulanti A-B-C.

FCM - Compliant with European Regulation 10/2011 for Simulants A-B-C.

FITT ALIFLEX SUPERFLEX

Marcatura | Marking: FITT ALIFLEX SUPERFLEX Øxx REG. (EU) 10/2011 A-B-C  PHTHALATE FREE - MADE IN ITALY

Ø interno Ø internal [mm]	Ø esterno Ø external [mm]	Spessore Thickness [mm]	Pressione d'esercizio Working pressure [bar]	Pressione di scoppio Bursting pressure [bar]	Vuoto Vacuum [mH ₂ O]	Raggio di curvatura Bending radius [mm]	Lunghezza Length [m]	Peso nominale Weight per meter [g/m]	Pezzi per pallet Pieces per pallet [pcs]	Dimensione pallet Pallet dimension [cm]
20	25,4	2,7	7	21	6	100	50	210	20	80x120
25	30,6	2,8	7	21	6	120	50	280	20	120x120
30	36	3	7	21	6	140	50	350	12	120x120
35	41,2	3,1	7	21	6	170	50	425	7	120x120
40	47	3,5	6	18	6	200	50	510	4	80x120
45	52	3,5	6	18	6	230	50	570	3	80x120
51	58,6	3,8	6	18	6	250	50	730	4	120x120
60	68,2	4,1	6	18	6	320	50	900	3	120x120
70	78,8	4,4	5	15	6	360	50	1125	3	120x120
76	85	4,5	5	15	6	400	50	1270	3	120x120
80	89,2	4,6	4	12	6	430	30	1450	3	120x120
90	100	5	4	12	5	490	30	1700	3	160x80
100	110,4	5,2	4	12	5	550	30	1950	3	160x80
110	120,8	5,4	3	9	5	600	25	2100	3	160x160

Pressione di scoppio e di esercizio a 23°C | Working and Bursting pressure at 23°C

Diametri interni e tolleranze corrispondenti sono in conformità alla norma UNI EN ISO 1307 in vigore. La tolleranza della lunghezza è ± 5%.
Inner diameters and corresponding tolerances according to the current standard UNI EN ISO 1307. The length tolerance is ± 5%.

Legenda conformità normativa: 1. Regolamento REACH (EC) n. 1907/2006 / 2. Direttiva RoHS / 3. Regolamento AIPS GS 2019:01 IPA - Categoria 2 / 4. Senza ftalati (<0.1% peso/peso)
Regulatory compliance legend: 1. REACH Regulation (EC) n. 1907/2006 / 2. RoHS Directive / 3. AIPS GS 2019:01 Regulation IPA - Category 2 / 4. Phthalate free (<0.1% weight/weight)